

# Technical specifications

---

## ENGINE SPECIFICATIONS

Data	Petrol
Number of cylinders	6
Displacement cc's	3192
Firing order	1-5-3-6-2-4
Compression ratio	10.8:1
Power output kW (PS)	171 (233) at 6300 rpm
Maximum torque Nm	317 at 3200 rpm

Data	Diesel	Diesel with DPF
Number of cylinders	4	4
Displacement cc's	2179	2179
Firing order	1-3-4-2	1-3-4-2
Compression ratio	16.5:1	16.5:1
Power output kW (PS)	118 (160) at 4000 rpm Belgium 110 (150) at 4000 rpm	112 (152) at 4000 rpm Belgium 110 (150) at 4000 rpm
Maximum torque Nm	400 at 2000 rpm	400 at 2000 rpm

# Technical specifications

---

## WEIGHTS

Variant	Approximate unladen weight <sup>1</sup>	Gross Vehicle Weight (GVW) <sup>2</sup>	Gross Train Weight <sup>3</sup>
Petrol	1825 kg 4020 lbs	2505 kg 5520 lbs	4505 kg 9930 lbs
Diesel	1820 kg 4010 lbs	2505 kg 5520 lbs	4505 kg 9930 lbs

<sup>1</sup> This figure includes the tool kit, all fluids to the correct levels, and spare wheel, but excludes the driver and passengers.

<sup>3</sup> The maximum permissible weight of the vehicle and braked trailer including their respective loads.

<sup>2</sup> The maximum permissible weight of the vehicle including passengers and load.


Variant	Maximum front axle load <sup>1</sup>	Maximum rear axle load <sup>1</sup>	Maximum roof rack load <sup>2</sup>	Maximum payload
Petrol and Diesel	1310 kg 2885 lbs	1360 kg 2995 lbs	75 kg 165 lbs	500 kg 1100 lbs

**Note:** <sup>1</sup> The front and rear axle maximum loads can not be reached simultaneously as this will exceed the GVW limit.

<sup>2</sup> This figure includes the weight of the roof rack.

# Technical specifications

## DIMENSIONS



E82384

Item	Description	mm/inches	Degrees
1	Width	2180/85.7	-
1	Width with mirrors folded	2005/78.8	-
2	Maximum height (Inc. roof rails)	1830/72.1	-
3	Approach angle	-	31°
4	Breakover angle	-	157°
5	Wheelbase	2660/104.7	-
6	Length excluding number plate plinth	4500/177.1	-
7	Track - front	1601/63	-
7	Track - rear	1614/63.5	-
8	Departure angle without tow hitch	-	34°
8	Departure angle with detachable tow ball	-	18°
-	Turning circle (kerb to kerb)	11.3m/37.1ft	-
-	Maximum wading depth	500/19.7	-

**Note:** Fitment of the sports styling pack will affect the off-road capability of the vehicle.

# Technical specifications

---

## Wheel alignment data (China only)

Wheel alignment - front	Wheel alignment - rear	Camber - front	Camber - rear	Castor - front and rear
+0.30°	+0.46°	-0.5°	-1.95°	Non-adjustable

## Clutch and brake pedal travel (China only)

The clutch and brake pedal travel are set at the factory and non-adjustable.