

Vehicle	Wheel	Tire	Tire Pressure – bar – (lbf/in <sup>2</sup> )			
			Normal		Gross Vehicle Weight	
			Front	Rear	Front	Rear
<b>RANGE ROVER – 2007 MY onwards</b>						
	7.5J X 18	255/60R 18 112V	2.3 – (33)	2.5 – (36)	2.5 – (36)	2.9 – (42)
	8.0J X 18	255/60R 18 112V				
	8.0J X 19	255/55R 19 111V				
	8.5J X 20	255/50R 20 109Y				
NAS/Canada/Gulf	8.0J X 19	255/55R 19 111V	–	–		
	8.5J X 20	255/50R 20 109Y				
Steel Space Saver	5.5J X 19	175/80R 19 122M	4.2 – (60)	4.2 – (60)	4.2 – (60)	4.2 – (60)

Notes

Vehicle	Wheel	Tire	Tire Pressure – bar – (lb/in <sup>2</sup> )			
			Normal		Gross Vehicle Weight	
			Front	Rear	Front	Rear
<b>RANGE ROVER SPORT – 2007 up to 2010 MY</b>						
	7.0J X 17	235/65R 17 108H	2.3 – (33)	2.5 – (36)	2.6 – (38)	2.9 – (42)
	8.0J X 18	255/55R 18 109V				
	9.0J X 19	255/50R 19 107Y				
	9.5J X 20	275/40R 20 106Y				
Durable Spare	8.0J X 19	255/55R 19 109Y				
Alloy Space Saver	5.5J X 19	175/80R 19 122M	4.2 – (60)	4.2 – (60)	4.2 – (60)	4.2 – (60)
<b>RANGE ROVER SPORT – 2010 MY onwards</b>						
	9.0J X 19	255/50R 19 107Y	2.3 – (33)	2.5 – (36)	2.6 – (38)	2.9 – (42)
	9.5J X 20	275/40R 20 106Y				
NAS/Canada	9.0J X 19	255/50R 19 107V	–	–	2.7 – (39)	3.0 – (43)
	9.5J X 20	275/40R 20 106Y	–	–	2.6 – (38)	2.9 – (42)
Gulf	9.0J X 19	255/50R 19 107Y	–	–	2.6 – (38)	2.9 – (42)
	9.5J X 20	275/40R 20 106Y	–	–	2.6 – (38)	2.9 – (42)
Durable Spare	8.0J X 19	255/55R 19 109Y	2.3 – (33)	2.5 – (36)	2.6 – (38)	2.9 – (42)
Alloy Space Saver	5.5J X 19	175/80R 19 122M	4.2 – (60)	4.2 – (60)	4.2 – (60)	4.2 – (60)

Vehicle	Wheel	Tire	Tire Pressure – bar – (lbf/in <sup>2</sup> )			
			Normal		Gross Vehicle Weight	
			Front	Rear	Front	Rear
<b>DISCOVERY 4 / LR4 – 2010 MY onwards</b>						
	7.0J X 17	235/70R 17 111H	2.3 – (33)	2.5 – (36)	2.5 – (36)	2.9 – (42)
	8.0J X 18	255/60R 18 112V				
	8.0J X 19	255/55R 19 111V				
	8.5J X 20	255/50R 20 109Y				
NAS/Canada/Gulf	8.0J X 19	255/55R 19 111V	–	–	2.5 – (36)	2.9 – (42)
	8.5J X 20	255/50R 20 109Y	–	–	2.5 – (36)	2.9 – (42)
Steel Space Saver	5.5J X 19	175/80R 19 122M	4.2 – (60)	4.2 – (60)	4.2 – (60)	4.2 – (60)
<b>DISCOVERY 3 / LR3 – 2007 up to 2010 MY</b>						
	7.0J X 17	235/70R 17 111H	2.3 – (33)	2.5 – (36)	2.3 – (33)	2.9 – (42)
	8.0J X 18	255/60R 18 112V				
	8.0J X 19	255/55R 19 111V				
Steel Space Saver	5.5J X 19	175/80R 19 122M	4.2 – (60)	4.2 – (60)	4.2 – (60)	4.2 – (60)

Notes

Vehicle	Wheel	Tire	Tire Pressure – bar – (lbf/in <sup>2</sup> )			
			Normal		Gross Vehicle Weight	
			Front	Rear	Front	Rear
<b>FREELANDER 2 / LR2 – 2007 MY onwards</b>						
	6.5J X 16	215/75R 16 107H or 103H	–	–	2.2 – (32)	2.2 – (32)
	7.5J X 17	235/65R 17 104V or 108V				
	8.0J X 18	235/60R 18 103V or 107V				
	8.0J X 19	235/55R 19 105V	–	–	2.4 – (35)	2.4 – (35)
NAS/Canada	8.0J X 19	235/55R 19 101H / 105H	–	–		
Steel Space Saver	7.0J X 17	225/65R 17 102H	–	–	2.3 – (33)	2.3 – (33)

**Note:** FREELANDER 2 – tire load capacity depends on tire manufacturer.

**Notes**

Vehicle	Wheel	Tire	Tire Pressure – bar – (lbf/in <sup>2</sup> )			
			Normal		Gross Vehicle Weight	
			Front	Rear	Front	Rear
<b>DEFENDER – 2007 MY onwards</b>						
90 Model	5.5F X 16	7.5 R16 C 108N **	-	-	2.1 – (30)	2.6 – (38)
		7.5 R16 C 116				
		205/80 R16 104T *				
	5.5J X 16	7.5 R16 C 108N **				
		205/80 R16 104T *				
	6.5J X 16 H2	235/85 R16				
7J X 16 Alloy						
						<b>Continued over.....</b>

**Note:** \* December 2008 – 205/80 R16 discontinued.

**Note:** \*\* April 2009 – 7.5 R16 C (108N) replaced by (112S) and fitment to 'F' rim discontinued.

**Note:** August 2009 – (120Q) replaced by (112Q) or (114Q).

**Notes**

Vehicle	Wheel	Tire	Tire Pressure – bar – (lbf/in <sup>2</sup> )			
			Normal		Gross Vehicle Weight	
			Front	Rear	Front	Rear
<b>DEFENDER – 2007 MY onwards</b>						
110 Model (see below for 110 Heavy Duty)	5.5F X 16	7.5 R16 C 108N **	2.1 – (30)	3.3 – (48)	2.1 – (30)	4.5 – (65)
		7.5 R16 C 116N				
	5.5J X 16	7.5 R16 C 108N **				
	6.5J X 16 H2	235/85 R16				
7J X 16 Alloy						
130 Model and 110 Heavy Duty	6.5J X 16 TT	7.5 R16 C 116N	–	–	3.1 – (45)	4.5 – (65)
	6.5J X 16 H2	7.5 R16 C 116N				
		235/85 R16 114Q				

**Note:** \* December 2008 – 205/80 R16 discontinued.

**Note:** \*\* April 2009 – 7.5 R16 C (108N) replaced by (112S) and fitment to 'F' rim discontinued.

**Note:** August 2009 – (120Q) replaced by (112Q) or (114Q).

**Notes**